

RJW Chemical Agitation Tank



WELL-TECH EQUIPMENT
威尔国际矿业装备

Brief Introduction

With only paddle wheel and dam-board settled in it, according to the unique design of impeller, stirring and mixing become more effective. It is suitable for the factories that need stuff dissolution, ore pulp store and gold leaching. In addition, the product can also be applied to construction and chemical industries.

Remark

The non-standard product shall be designed and made for the customer's need, if there is no special requirement, the normal models shall be provided.

/Main Technical Parameters

Model	Effective Capacity (m ³)	Impeller Rotating Speed (rpm)	Impeller Diameter (mm)	Motor Model	Motor Power (kw)	Weight (kg)
BJW-500x500	0.074	525	240	Y80M2-4	0.75	142
BJW-750x750	0.25	530	240	Y80M2-4	0.75	280
BJW-1000x1000	0.58	513	230	Y90S-4	1.1	420
BJW-1200x1200	1.4	401	380	Y112M-6	2.2	700
BJW-1500x1500	2.2	320	400	Y132S-6	3	1265
BJW-2000x2000	5.46	230	550	Y132M2-6	5.5	1850
BJW-2500x2500	12.26	230	630	Y160M-6	7.5	2681
BJW-3000x3000	17.5	200	800	Y225S-8	18.5	4620
BJW-3500x3500	29.5	190	850	Y225M-8	22	5380
BJW-4000x4000	46	200	1000	Y250M-8	30	7850